ECO2L3A

3-1/2" ECO²LED Series

Round Adjustable Trim

Project Notes Fixture Type Date

SPECIFICATIONS

COLOR TEMPERATURE	2,700K or 3,000K
CRI	80 + 90 +
LED MODULE	Lumiled Luxeon CoB 9W, delivers a lumen maintenance greater than 70% after 50,000 hours of operation (L_{70}). Provides a clean white light without pixilation and produces a high quality true color, inside 3 steps MacAdam ellipse.
LUMENS OUTPUT	Up to 740 Lumens, 69 Lms/W
LIFESPAN	50,000 hours
TRIM	Powder coat painted or plated die-formed steel. Different finishes available. Painted finishes available with Marine Grade option.
BEAM	M: Narrow Flood → 30° W: Wide Flood → 54°
HEAT SINK	High quality injected aluminum ensuring maximum heat dissipation.
CEILING CUTOUT	Ø 3-5/8" (92 mm)
COMPATIBLE HOUSINGS	IC and Airtight Remodel Housing: ECO2REL300 IC and Airtight New Construction Housing: ECO2NWL300 IC and Airtight Box: ECO2ISL300
CERTIFICATION	 cULus E343977 for damp locations Energy Star® certification (pending) Title 24 compliant
WARRANTY	5-year warranty on ECO ² LED Module and Driver.



ECO2L3A-04BR (illustrated)



















