

Fuzzy Solutions: Safe, High-performance Enclosures with No Foam

Dr John Straube, P.Eng.
Principal, RDH Building Science
Associate Professor, University of Waterloo




UNIVERSITY OF
WATERLOO


Department of Civil and
Environmental Engineering
Architectural Engineering

2

Outline



- Why foam
- Alternate designs with no foam
- Walls
- Roofs
- Basements
- Retrofits
- Field measurements of performance



WATERLOO
ENGINEERING


3

Why foam?


- XPS, EPS, ccSPF, ocSPF, PIC
- Stiff, easy to handle
- Vapor resistant (most)
- Air resistant
- Water resistant
- Often cheapest

Non-foam designs


- Often can use rigid stonewool
 - stiff and strong boards depends on density
 - stonewool is moisture tolerant
- But...
 - Cellulose, straw, and batt need to be protected
 - All fibrous insulation designs need to adjust for lack of vapor resistance



6



7



8

Effective Assembly R-value of Split Insulation Wall Assembly [ft ² ·°F·hr/Btu]		
	2x4 Stud Wall (R-12 Batts)	2x6 Stud Wall (R-19 Batts)
Thickness of Exterior Insulation	R-value/inch of Exterior Insulation	
	R-4.0	R-4.0
0"	11.3	16.2
1/2"	13.3	18.2
1"	15.3	20.2
1 1/2"	17.3	22.2
2"	19.3	24.2
2 1/2"	21.3	26.2
3"	23.3	28.2
3 1/2"	25.3	30.2
4"	27.3	32.2
4 1/2"	29.3	34.2
5"	31.3	36.2
5 1/2"	33.3	38.2
6"	35.3	40.2

A 23% framing factor is assumed which is consistent with standard 16" o.c. stud framing practices.

Air control
 Water control

RDH
 Building Science

9





10



11

Resources




12

Service wall



- Locates air (maybe vapor) membrane inside structure
- Harder to seal flexible unsupported membrane




13

Deep stud w/service wall

Effective Assembly R-value for Deep Stud Walls [ft ² ·°F·hr/Btu]				
Thickness of Wall Framing	Uninsulated Service Wall		Insulated (R-12) 2x4 Service Wall	
	R-3.4	R-4.0	R-3.4	R-4.0
2x6	17.7	18.9	25.2	26.3
2x8	21.9	23.5	29.4	31.0
2x10	26.7	28.7	34.2	36.2
2x12	31.6	34.0	39.0	41.5
9.5" I-joist	28.4	31.2	35.9	38.7
11-7/8" I-joist	35.4	39.2	42.9	46.7
14" I-joist	41.7	46.3	49.1	53.8
16" I-joist	47.6	53.0	55.0	60.5

A 23% framing factor is assumed which is consistent with standard 16" o.c. stud framing practices. Reduced framing factors may be possible.
Floor joist details will often degrade these values





WATERLOO ENGINEERING

14

Effective Assembly R-value for Double 2x4 Stud Wall* [ft ² ·°F·hr/Btu]			
Thickness of Gap Between Stud Walls	R-value/inch of Insulation		
	R-3.4	R-4.0	R-5.0
0"	19.7	21.2	
1/4"	20.5	22.2	
1/2"	21.4	23.2	
1"	23.1	25.2	
1 1/2"	24.8	27.2	
2"	26.5	29.2	
2 1/2"	28.2	31.2	
3"	29.9	33.2	
3 1/2"	31.6	35.2	
4"	33.3	37.2	
4 1/2"	35.0	39.2	
5"	36.7	41.2	

Double stud





Assumes interior stud wall has the same 23% framing factor as the exterior stud wall, though it may require less framing
Floor joist details can degrade these values

WATERLOO ENGINEERING

15

From: *Mid-Rise 2.0, Innovative Approaches to Mid-Rise Wood Frame Construction*. Canada Wood Council

Euro House ..

- Well-insulated but risky
- Lots of complexity
- Challenging air barrier
- Continues 1980's approach
- Hard won building science being ignored

16


Fig. 2.4: Floorline junction

From: *Mid-Rise 2.0, Innovative Approaches to Mid-Rise Wood Frame Construction*. Canada Wood Council


only responsible for the HRV installation from the roof, down the vertical shafts to the silencer box located on the inside wall of each suite (Fig. 2.6).

Fig. 2.5: View showing vapour barrier wrapped over floor lines

17




18




19

ROOFS


20



21



22



23

Cathedral ceilings


- Strap- and counter-strap allows ventilation even around valleys, dormers etc



WATERLOO
ENGINEERING


24

Low-slope Roof Assemblies





25

Doing it right



Hidden rain shedding



Lapped rain shedding

Structural Support / Backup


Primary air-water

WATERLOO ENGINEERING



Courtesy Cosella-Doerken

26

Unvented roof



- Similar to wall design



Air control

Water control

WATERLOO ENGINEERING

27

Exterior insulation, roof underlayment




28




29

BASEMENTS


30



31



32



33




34




35



36




37



38




39



40


FIELD STUDY

41




U of Waterloo Field study

- Assess high R-value walls of future
- Moisture performance
 - Risk of condensation?
 - Tolerance to wetting (drying)?
- Included all fibrous solutions


42


42




R-values

- Four fibrous insulations
- Walls 5 & 6 have no 6 mil poly vapor barrier

Wall	Cavity W/m ² K	Stud W/m ² K	Effective U W/m ² K	R-imp
1. Double Stud R44	0.124	0.256	0.150	37.7
2. I-Joist R44	0.156	0.213	0.167	33.9
3. 2x6 Datum	0.228	0.602	0.303	18.7
4. 2x8 ccSPF R40	0.148	0.492	0.217	26.2
5. 2x6 PIC R22 batt	0.154	0.264	0.176	32.2
6. 2x6 2.5" XPS	0.153	0.261	0.175	32.5
7. 2x6 3" MFI	0.152	0.257	0.173	32.8


43

43




44




45



46




47




Results


- Measured for over two years
 - Currently undergoing spring rain wetting
 - Drill down on drying performance
- More results will be developed


48


48




49




50




51



52



53



54

Thank you!

SEE US ON THE WEB
→ rdh.com | buildingsciencelabs.com

RDH Building Science

55